







| Technical Specification                           |       |               |
|---|-------|---------------|
| Height  | 165mm |               |
| Width   | 55mm  |               |
| Depth   | 25mm  |               |
| Weight  | 182g  |               |
| Standards   |       |               |
| BS EN 60900 , VDE 682/201, ASTM-F 1505 , ISO 5749 |       |               |
| CE certified (Y/N)                                |       | No            |
| UKCA certified (Y/N)                              |       | No            |
| REACH Content Status                              |       | SVHC free     |
|   |       |               |
|   |       |               |
| Barcode   |       | 5051178107829 |
| Commodity Code                                    |       | 8203200000    |
| Warranty Term                                     |       | 12 months     |
|   |       |               |

## **AC0888**

**VDE Side Cutter 160mm** 

- ~ Two component, ergonomic design, with anti-slip horns for increased comfort, control & safety
- ~ Induction hardened jaws for outstanding long term performance
- ~ Cutting jaws with C.K optimised geometry for unsurpassed cutting performance
- ~ Special alloy steel, drop forged, hardened & tempered for exceptional strength & durability
- ~ VDE approved

Users are advised to regularly examine their VDE tools. Even the slightest damage can compromise the insulation integrity and potentially expose the user to the risk of injury or even death.

10-AC0888-2021-V1

