

## 1 - Wiring Accessories





| Technical Specification |                                |
|-------------------------|--------------------------------|
| Plate Dimensions        | 146mm (W) x 88mm (H) x 8mm (D) |
| Maximum Voltage         | 250V~ 50Hz                     |
| Load Rating             | 13A                            |
| Fixing Centres          | 120.6mm                        |
| Terminal Torque         | 1.2Nm                          |
| Terminal Capacity       | 3 x 2.5mm² or 2 x 4mm²         |
| Single Pole             | Yes                            |
| Twin Earth Terminals    | Yes                            |
| USB Charging Output     | 5V DC, 4.2A Total              |
| USB Type                | USB Type "A" & Type "C"        |
| USB Standby Current     | 2mA                            |
| Product Markings        | DC, 5V 3A, 5V 2.4A max, 4.2A   |
| Operational Temp.       | -5°C to +40°C                  |
| Warranty                | 10 Years, 1 Year Electronics   |
|                         |                                |

## AC12310

## 2G Sw. Safety Skt + USB's

- Victorian style plate
- · Satin chrome finish
- 3 pin safety shuttered socket outlets. All 3 pins of the plug must be inserted for the shutters to open
- · Supplied with white gasket
- Type A & Type C USB outlets provided
- Independent Charging: 5V DC, 4.2A USB Type A (2.4A), USB Type C (3A)
- Fits on to 25mm deep backbox
- The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V

1-AC12310-2021-V1

