



Dimensional/Line drawings to go here

### AC2996

### Selekt-A-Box

Selection Of Push-In And Piano Key Connectors  
 Ideal For A Quick, Reliable, Easy And Convenient  
 Way For Installation Of Cable Conductors  
 Can Be Applied Without The Need Of Any Tooling  
 For Use On Both Solid And Flexible Conductors  
 Transparent Housing Allows A Fast And Easy  
 Visual Check  
 RoHS Compliant  
 EN 60998-1:2001  
 UL And CSA Approved

#### Technical Specification

|                        |                                    |
|------------------------|------------------------------------|
| Cable Range Solid      | 0.75mm - 2.5mm                     |
| Cable Range Flexible   | 1.5mm - 2.5mm                      |
| Voltage Rating         | 400V and 600V                      |
| AMP Rating             | 20 and 24AMP                       |
| Colour                 | Orange, Blue, Black And Grey       |
| Number Of Connections  | 2, 4, 6 and Way                    |
| Cable Range            | 0.75mm - 2.5mm ( 3 Way Piano Key ) |
| Operating Voltage      | 400V AC ( Piano Key )              |
| Operating Current      | 32AMP ( Piano Key )                |
| Operating Temperature  | -30C to +110C ( Piano Key )        |
| Cable Stripping Length | 10mm ( Piano Key )                 |
| Housing Material       | Plastic GWT 960C ( Piano Key )     |
| Contact Material       | Electrolytic Copper ( Piano Key )  |
| Spring Material        | Hardened Steel ( Piano Key )       |

**2-AC2996-2021-V1**