



**Acel part number (AC35133)**

**RCBO 20A 30mA 10kA C curve type A**

### Features and benefits

Type A, C Curve  
10kA  
750mm neutral lead  
din rail mounting

### Technical Specification

| Attribute                              | Value                     |
|----------------------------------------|---------------------------|
| STANDARD                               | IEC/EN 61009-1            |
| NUMBER OF POLES                        | 1P+N (Switched)           |
| RATED VOLTAGE (Un/AC)                  | 230V                      |
| FREQUENCY (Hz)                         | 50/60                     |
| RATED BREAKING CAPACITY (Icn)          | 10000A (10kA)             |
| TRIPPING CHARACTERISTICS               | B CURVE : 3-5In, C 5-10IN |
| RESIDUAL CURRENT CHARACTERISTICS       | TYPE A (AC AND PULSATING) |
| RATED RESIDUAL OPERATING CURRENT (IΔn) | 0.03                      |
| MECHANICAL ENDURANCE                   | 20,000 / 4,000            |
| PROTECTION DEGREE (IP)                 | 20                        |
| FLYING NEUTRAL CABLE LENGTH (mm)       | 750mm                     |
| MOUNTING                               | 35mm din rail             |
| MATERIAL                               | PA6 (Nylon 6)             |
| WEIGHT (1PC) Kg                        | 0.2                       |

**3-AC35133-2024-V1**