



### AC38017

#### 22 Way Cons. Unit + Iso. Sw +

- Split load board with surge protection
- Metal consumer unit enclosure
- White finish (RAL 9003)
- Mains tail clamp fitted as standard
- 100A Mains Switch fitted
- 2 x 80A 30mA RCD fitted
- 2 Pole 40kA SPD fitted
- 2 x Blanks Supplied ( Product Code: AC38070)
- 14 free ways
- 10 year warranty (3 year warranty for devices)

#### Technical Specification

|                         |                                   |
|-------------------------|-----------------------------------|
| Dimensions With Door    | 474mm (W) x 260mm (H) x 115mm (D) |
| CU Knockouts (Top)      | 7 x Ø20mm, 2 x Ø25mm & 2 x Ø40mm  |
| CU Knockouts (Bottom)   | 7 x Ø20mm, 2 x Ø25mm & 2 x Ø40mm  |
| CU Knockouts (Sides)    | 1 x Ø32 & 1 x Ø40                 |
| CU Knockouts (Rear)     | 3 x 100mm x 60mm                  |
| Nominal Voltage         | 230V~ 50/60Hz                     |
| Tail Clamp Capacity     | 25mm <sup>2</sup>                 |
| Tail Clamp Torque       | 1.5Nm                             |
| Main Sw. Terminal Cap.  | 35mm <sup>2</sup>                 |
| Main Sw. Terminal Torq. | 2.5Nm                             |
| RCD Terminal Capacity   | 25mm <sup>2</sup>                 |
| RCD Terminal Torque     | 2.5Nm                             |
| SPD Terminal Capacity   | 35mm <sup>2</sup>                 |
| SPD Terminal Torque     | 2.0Nm                             |
| Operational Temp.       | -5°C to +40°C                     |

**3-AC38017-2022-V1**