



## AC43845

### Downlight fire rated tilt 3/5W 3CCT IP65 white bezel

#### Features & Benefits

- Two wattage and three colour selectable from remote driver
- Two-part first fix connector with dedicated testing terminals
- Double hinged terminal for easy access to terminal blocks
- Tested for use in Solid, I-Joist and Steel Open Web joist ceilings
- 20° tiltable adjustment
- Triac dimmable as standard, see JCC.co.uk for approved dimmer list

#### Technical Specifications

|                                |                          |
|--------------------------------|--------------------------|
| Actual Lumen Output            | 480/700                  |
| Class                          | II                       |
| Color Finish                   | White                    |
| Correlated Color Temperature   | 3000/4000/5700K          |
| Diameter (mm)                  | 100                      |
| Dimmable                       | Yes, Triac dimmable only |
| Height (mm)                    | 58.4                     |
| IP Rating                      | IP65                     |
| LED Life (Hours)*              | 88000                    |
| Length (mm)                    | 547                      |
| Lumens Per Circuit Watt        | 160/140                  |
| Luminaire Circuit Wattage      | 3/5 selectable           |
| Operating Temperature Range °C | 0 to 26                  |
| Product Aperture Size          | 83mm Ø                   |
| Voltage Rating                 | 230-240                  |

4-AC43845-2025-V1

