



## AC447155

### LED panel, IP20, 5000K

- Suitable for use in offices, shops, reception areas, restaurants, hotels, schools, hospitals
- LED replacement for 4x18W T8 lay-in modular
- A high quality PP thermoplastic diffuser ensures that light transmission is maximised into the lit space and provides a TP(a) rating to comply with fire regulations
- Fits into standard sizes of ceiling grid - 15mm and 24mm
- High efficacy of 101lm/W
- Wide operating ambient temperature range of -20°C to +40°C
- 50,000 hour average lamp life. Up to 5 times that of a standard fluorescent lamp
- Driver complete with male and female loop in/out connectors included for fast fix installation
- Suspension kit available
- Suitable for switching by PIR, Microwave or Photocell
- 1-10V and DALI dimmable driver and 3 hour emergency options available

#### Technical Specification

Cap Type	LED
Total Power	37.7
Lumens (lm)	3800
Beam Angle	110
Lamp Life (Hrs)	50000
Number of LEDs	196 (14S14P)
Comparable To	4x18W Fluorescent
CRI	80
CCT (K)	5000
Efficacy (lm/cctW)	101
Lux at 1m	1310
Power Factor	0.97
Colour	White
Width (mm)	595
Depth (mm)	10

**4-AC447155-2021-V1**

