



AC448000

9w LED DD lamp 2pin Tri-CCT

Features and Benefits:

- CCT switchable (2700k/4000k/6500k)
- For maximum energy savings, bypass all control gear and supply directly from the mains
- Save energy up to 65% compared with a fluorescent lamp with magnetic ballast
- Single side high lumen output for light anywhere its needed
- Long life of 30,000h
- Compatible with emergency modules (Standard AC44897 and Self-testing AC44863)
- Instant start
- Negligible UV output
- Mercury free

Technical Specification

Wattage	9w
Lamp Cap	GR8
Voltage	220-240 Vac 50-60 Hz
Current	43 mA
CCT options	Colour Switchable (2700k/4000k/6500k)
Nominal Luminous Flux	1050lm/1130lm/1050lm
Nominal Lifetime	30,000
Dimmable	No
Switching Cycles	50,000
Warm-up time to 60%	Instant full light
Diameter	145x145mm
Rated Peak Candelas (cd)	350
Power Factor	0.90
LMF at Nominal Lifetime	0.75
SDCM of CCT	<6
CRI	>83
Start Time	0.39s
Ambient Temperature	-20 to 40 degree
Emergency Module	AC44897 (Standard) and Self Testing (AC44863)
Retrofit	Yes

4-AC448000-2023-V1

