




4 - Lamps & Lighting





Technical Specification	
Wattage	18w
Lamp Cap	GR10q
Voltage	220-240 Vac 50-60 Hz
Current	87 mA
CCT options	Colour Switchable (2700k/4000k/6500k)
Nominal Luminous Flux	2210lm/2400lm/2210lm
Nominal Lifetime	30,000
Dimmable	No
Switching Cycles	50,000
Warm-up time to 60%	Instant full light
Diameter	192x192mm
Rated Peak Candelas	590
(cd)	
Power Factor	0.90
LMF at Nominal Lifetime	0.75
SDCM of CCT	<6
CRI	>83
Start Time	0.39s
Ambient Temperature	-20 to 40 degree
Emergency Module	AC44897 (Standard) and AC44863 (Self-testing)

AC448004

18w LED DD lamp 4pin Tri-CCT

Features and Benefits:

- CCT switchable (2700k/4000k/6500k)
- For maximum energy savings, bypass all control gearand supply directly from the mains
- Save energy up to 65% compared with a fluorescent lampwith magnetic ballast
- Single side high lumen output for light onlywhere its needed
- Long life of 30,000h
- Compatible with emergency modules (Standard AC44897 and Self-testing AC44863)
- Instant start
- Negligib<mark>le UV</mark> output
- Mercury free

4-AC448004-2023-V1

