



## AC448150

### Narrow IP65 Wall Pack 15w

#### Features & Benefits

1. Compact and slim design
2. Anti-corrosion polycarbonate body
3. BESA box fitting points
4. Dusk to dawn senso
5. Durable and rugged IK10 Polycarbonate construction

#### Technical Specification

|                                      |                     |
|--------------------------------------|---------------------|
| Power                                | 15w                 |
| Voltage                              | 220-240 Vac 50-60Hz |
| Current                              | 71 mA               |
| Protection                           | Class I, IP65       |
| Power Factor                         | >0.94               |
| Luminous Flux                        | 1575 lm/ 1850 lm    |
| CCT                                  | 3000k / 4000k       |
| CRI                                  | >82 / > 84          |
| Lifetime                             | 40,000 h            |
| Switching Cycles                     | 50,000              |
| Start Time                           | 0.10s               |
| Warm-up time to 60%                  | Instant full light  |
| Diffuser                             | White opal diffuser |
| Lumen Maintenance Factor at Lifetime | 0.75                |
| Ambient Temperature (degree)         | -20 to 40           |
| Housing                              | Polycarbonate       |
| Beam Angle (degree)                  | 120                 |
|                                      |                     |
|                                      |                     |
|                                      |                     |

4-AC448150-2022-V2

