




AC44835

10/15/18w Flat Downlight

Features and Benefits:

- Surface or cut-out mounting (Adjustable cut-out 65-205mm)
- Switchable CCT (3000/4000/6500k)
- Switchable wattage (10/15/18w)
- Class II IP20
- High efficiency of 94lm/W
- Long life of 30,000 h
- Instant Start
- IP44



Technical Specification

Wattage	10w/15w/18w
Voltage	220-240 Vac
Current	87 mA / 130 mA / 157 mA
Inrush Current	127 Aat 840 ns
CCT options	3000k / 4000k / 6500k
Nominal Luminous Flux	10w (1000lm-1100lm), 15w (1400lm-1500lm), 18w (1600lm-1700lm)
Nominal Lifetime	30,000
Protection	Class II IP44
Connection	Wiring Leads (29 cm)
Flicker Percent	1%
Beam Angle	120 degree
Dimmable	No
Switching Cycles	50,000
Warm-up time to 60%	Instant full light
Diameter x Depth	230 mm x 21.5 mm
Power Factor	0.50
LMF at Nominal Lifetime	0.75
SDCM of CCT	<6
CRI	>80
Start Time	0.49s
Ambient Temperature	-20 to 40 degree

4-AC44835-2021-V1

