



AC55687

Emergency Exit Sign

Features and benefits:

The AC55687 emergency exit sign gives a streamlined installation and is further enhanced by our unique remote control testing option. It can be installed in both switchable maintained or non-maintained option.

Features:

Prismatic diffuser on underside to illuminate exit door.

Easy Installation and minimal maintenance.

Optional remote control testing facility.

Maintained or Non-maintained 3 hour back-up.

Incorporates LiFePo4 3.2v 1000mAh.

Low environmental impact.

Meets BS EN 60598-2-22 and other relevant standards.

Additional legends available (AC5688 - Right, AC5689 - Left, AC5690 - Down).

Remote Control:

Using the AC5697 optional remote allows both monthly 5 second & annual 3-hour test. Fittings can be tested from up to 7m away.

Technical Specification

Attribute	Value
Light Source	4w SMT LED
IP rating	IP20
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz \pm 10%
Mains current	(Max) 150mA 35mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per BS EN 60598-2-22
Temperature range	5 TO 40 °C
Weight	650gm
Battery	LifePo4 3.2v 1000mAh
Size	317W x 185H X 29mmD
Viewing distance	32m

5-AC55687-2025-V1