

5 - Emergency Lighting, Fire & Safety







| Technical S <mark>pecif</mark> ication | n |
|--|---|
| Light Sou <mark>rce</mark> | 3w SMT LED |
| IP rating | IP50 |
| Emergency Duration | 3-Hours (minimum) |
| Mains voltage | 230v 50Hz ± 10% |
| Mains current | (Max) 150mA 35mA quiescent |
| Recharge period | Less than 24 hours |
| Charge indicator | Integral Green LED |
| Changeover voltage | As per requirements of BS EN 60598-2-22 |
| Temperature range | 5 TO 40 °C |
| Weight | 800gm |
| Battery | LiFePo4 3.2v 1500mAh |
| Size | 344W x 237H X 42mmD (Excludes brackets) |
| Viewing distance | 30m |
| | |
| | |

AC55714

5-IN-1 Emergency Exit Sign

The 5-in-1 emergency exit sign means you will always have the correct mounting method.

The 5-in-1 is supplied with a full legend set and is further enhanced by our unique remote control testing option. It can be installed in both switchable maintained or non-maintained option.

Features

- 5 Mounting options supplied as standard
- Wall
- Ceiling
- Flag
- Recessed
- Suspended
- Maintained or Non-maintained 3 hour emergency back-up
- Incorporates LiFePo4 3.2v 1500mAh battery
- Low environmental impact
- Minimal maintenance
- Meets BS EN 60598-2-22 and other relevant standards

Remote Control Option

Using the AC5697 optional remote control gives the following testing options.

The AC5697 is capable of testing any number of compatible emergency lights.

Allows both monthly 5 second & annual 3-hour test.

Fittings can be tested from up to $7 \mathrm{m}$

No need to fit key switches

Fitting will show a red LED if a fault is detected or Green for a pass

No need to wait for the test to complete, the indicators will remain lit until the next test or any fault is corrected.

Press once for 5 second monthly test Press twice for 3 hour yearly test LED confirms pass/fail status

5-AC55714-2024-V1

