



AC55716

Surface Emergency Downlight

The AC55716 is a 3 watt non-maintained surface environmentally friendly emergency downlight. The downlight comes with both open area and corridor lens options ensuring the correct fitting is always available. The inbuilt green charge LED gives great visibility of the charging state of the fitting. The AC55716 is further enhanced by our unique remote control testing option.

Features

- 3W Non-maintained
- Long life LED technology
- Non -maintained 3 hour emergency backup
- Twin Lenses supplied
- BESA box fixings
- Sleek & minimalistic design
- Screw-less terminals
- Low environmental impact
- Low maintenance
- Meets BS EN 60598-2-22 and other relevant standards
- Enhanced optical performance gives excellent spacing distances

Remote Control Option

Using the AC5697 optional remote control gives the following testing options.

The AC5697 is capable of testing any number of compatible emergency lights.

Allows both monthly 5 second & annual 3-hour test.

Fittings can be tested from up to 7m

No need to fit key switches

Fitting will show a red LED if a fault is detected or Green for a pass

No need to wait for the test to complete, the indicators will remain lit until the next test or any fault is corrected.



Technical Specification	
Light Source	3w SMT LED
IP rating	IP20
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz \pm 10%
Mains current	(Max) 150mA 35mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	0 TO 40 °C
Weight	320gm
Battery	LiFePo4 3.2v 3000mAh
Lumen output	150Lm (Open Area) 137Lm (Corridor)



5-AC55716-2024-V1

