



### AC55720

#### 5-IN-1 Self Test Exit Sign

The 5-in-1 emergency exit sign means you will always have the correct mounting method.

The 5-in-1 is supplied with a full legend set and is fully self testing.

It can be installed in both switchable maintained or non-maintained option.

#### Features

- . Monthly & Annual Self Test
- . 5 Mounting options supplied as standard
- . Wall
- . Ceiling
- . Flag
- . Recessed
- . Suspended
- . Maintained or Non-maintained 3 hour emergency back-up
- . Incorporates LiFePo4 3.2v 1500mAh battery
- . Low environmental impact
- . Minimal maintenance
- . Meets BS EN 60598-2-22 and other relevant standards



#### Technical Specification

Light Source	3w SMT LED
IP rating	IP50
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz $\pm$ 10%
Mains current	(Max) 150mA 35mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	5 TO 40 °C
Weight	800gm
Battery	LiFePo4 3.2v 1500mAh
Size	344W x 237H X 42mmD (Excludes brackets)
Viewing distance	30m

5-AC55720-2024-V1