

## 6 - Ventilation & Heating





Technical Specification	
Adjustable Timer	Yes
H (mm)	175
Input Power 1 (W)	20
Installation Type	Inline duct, Ceiling void, Ceiling
Lamp Type	LED
Mode	Intermittent
Profile	Standard
Room Type	En Suite, Bathroom, Utility
Speed Control Type	External, On/Off
Speed Control Type Speed (I/s)	External, On/Off 30.6
	·
Speed (I/s)	30.6
Speed (I/s) Spigot Dia (mm)	30.6 100
Speed (I/s) Spigot Dia (mm) Timer Max (min)	30.6 100 20

## AC6203

## LED shower light in-line centrifugal timer kit

Available with an integral mounting bracket. Designed to comply with the **Building Regulations on Ventilation (F1).** The fan range is powered by a single phase induction motor with pre-oiled bearings for a long, maintenancefree life. The Shower Kit comprises of the centrifugal in-line fan unit, 6 metres of PVC ducting and wall grilles. The Showerlite Kit comprises of the centrifugal in-line fan unit, 6 metres of **PVC** ducting and wall grilles together with a chrome Showerlite fitting and transformer. The fan has all the features of the fan unit, but has the additional benefit of a 120mm outlet, thus making it suitable for 125mm (5") ducting systems.

6-AC6203-2021-v1

