



### AC63013

## 2 speed 100mm axial fan kit

An intermittent extract humidistat / timer fan (adjustable between 50 and 90% RH; 30s to 30mins timer overrun) designed to control humidity, odours and mould growth in bathrooms, shower rooms, cloakrooms and toilets.

Supplied with a remote transformer, the fan is designed specifically for safe installation directly in or over splash area zone 1.

Meets Parts F and L of Building Regulations.

Suitable for wall, ceiling and window fitting (via a Simply Silent Window Kit Plus), the fan comes complete with a wall-fitting kit.

Features a grille-style fascia finished in cool white

Ghost Air Movement Technology for near-silent running.

The fan has 2 speeds, selectable at install and comes complete with a 2 year Guarantee.

### Technical Specification

Attribute	Value
Extract Performance (l/s)	15 / 21
Extract Performance (m3/hr)	54 / 76
Electrical Power Rating (W)	5.5 / 11.8
Specific Fan Power (W/l/s)	0.37 / 0.56
Sound Pressure (dBA @3M)	22/ 34
IP Rating	4
Fan Weight (Kg)	0.65
Fan Grille Height / Width (mm)	178.5
Fan Depth (mm)	122.2
Fan Spigot Diameter (mm)	98

6-AC63013-2023-V1

