



6 - Ventilation & Heating



Dimensional/Line drawings to go here

Technical Specification	
Element output	1307 W
Storage heater output	2831 W
Charge period	7H
Charging (7h)	19.8 kWh
Connection	240 V-
Frequency	50-60 Hz
Length	111 CM
Height	73 CM
Width	18 CM
Weight	147 KG
Num. of blocks (7.5kg)	16
Num. of blocks (11.5kg)	-
EAN13	8432336111228

AC6588

ECOSSH408

- o High heat retention storage heater.
- IEM technology, the intelligent way to manage the charge and the discharge.
- o Weekly and daily programming.
- Three levels of temperature: Comfort, Economy and Frost-protection.
- Open window detection for reduced energy waste.
- o Adaptive start control.
- High quality insulation materials with low thermal conductivity.
- Double high heat retention materials in all sides of the storage heater.
- o Temperature sensor with calibration option.
- Overheating protection on storage heating function.
- o Balancing heating element.
- o Safety thermostat with manual reset.
- o Class I insulation.
- Storage heating elements made of stainless steel.
- o Front, side and rear air isolating chambers.
- Storage core made of a specially designed material for Ecombi HHR.
- Steel structure powder coated in epoxy RAL 9010.
- o Robust thermoplastic fittings.
- o Easy to install on any kind of wall.
- Very intuitive keyboard with lock option.
 Compatible with two-period off peak electric tariff in a single 24-hour interval.

6-AC6588-2022-V1

