

6 - Ventilation & Heating



Dimensional/Line drawings to go here

Technical Specification	
Selectable Output (KW)	3-15 kW
Kcal/h	2580-12900 kcal/h
Current 3 X400 V+N-A	13-21.7
Current 230 V-A	113-52.2
Time Available DHW	29'04"-5'49"
Volatage (V)	3x400 V+N/220-240
Frequency (Hz)	50-60
Insulation	Class 1
Height	76 CM
Width	35 CM
Depth	265 CM
Weight	29.5 CM
EAN13	8432336804700

AC6592

MAS15

- Wall mounted heating boiler made of insulated steel.
- Modulating electronic control of the heater by SEM system (Smart Electronic Modulating system).
- Stainless steel shielded elements INCOLOY 800.
- o 6L heating expansion vessel.
- o Auto Heating Regulation mode.
- o Pressure gauge 0-4bar.
- o Circulating pump.
- o Auto air vent.
- o Silent TRIAC power switches.
- o Heating flow detector.
- o Heating temperature limiter 100°C.
- o Powder coated RAL 9010.
- Wall bracket steel template to set up connections easily.
- o Heating 3 bar relief valve.
- o Also suitable for use with under floor heating.
- Compatible with the Elnur "RSTAT" Ambient Thermostat and the Elnur Connected range of internet thermostats, all available as accessories.

6-AC6592-2022-V1

