



### AC66215

#### 2.88m<sup>2</sup> of Overlay Boards for Foil Mats

Overlay Boards allow the Combymat foil mats heating system to be installed beneath carpet, vinyl, linoleum and bonded board floors without needing to cover the heating system with a levelling compound.

By enabling a dry installation without any wet trade the system saves installation time and costs and also minimises build height; the total build height of the Combymat System with underlay, and the Overlay Boards, is only 13mm.

The Overlay Boards provide a strong and smooth floating floor which accepts carpet and most resilient floor coverings, and floor coverings can be changed if desired while leaving the heating system in place.

Technical Specification	
Board Dimensions	600mm x 1200mm
Overall Thickness	7mm +/- 0.2mm
Pack Coverage	2.88m <sup>2</sup>
Material	MDF coated with contact adhesive
Density	770 kg/m <sup>3</sup>
Bending Strength	40 kg/cm <sup>2</sup>
Weight	0.2 kg/m <sup>2</sup>
Compressive Strength	300kPA
Fire Class	EN 13501:2007 - E <sub>FL</sub>
Humidity	4 - 10%
Manufactured In	The Netherlands

- Dry and dust free installation
- Creates a very stable, floating sub-floor
- Precision cut for quick and trouble free installation
- Very simple to install
- Heating system and overlay boards can be installed in a single day
- Increase build height by only 7mm
- Pre-coated with a contact adhesive for speedy installation
- Suitable for use with carpet, vinyl, linoleum and bonded board floors
- A simple one person job to install

**6-AC66215-2021-V1**

