

## 6 - Ventilation & Heating





Technical Specification	
Capacity	5 litres
Power	2 kW
Outer Casing	Easy clean high impact plastic
Controls	Thermostat adjustable to 75°C
Safety	Overheat temperature protection (manual reset)
ErP Energy Efficiency	Class B
Heat Up Time	6 mins (70% tank capacity 10°C - 60°C)
Standing Loss	0.51 kWh/ day
IP Rating	IPX4
Water Pressure	Minimum water pressure 0.5 bar, maximum water pressure 4.2 bar
Electrical Connection	Cable pre-wired (1.5m)
Dimensions	h x w x d (mm) 320 x 280 x 245
Approvals	CE, UKCA, WRAS
Warranty	1 year parts or replacement warranty

## AC69401

## **5 Litre Unvented Water Heater**

- Compact 5 litre capacity
- For hand washing at a single basin
- 2.0 kW element
- Mains pressure flow rates
- ErP Energy Efficiency class B
- Can be used with regular taps including mixers
- Neon element on indicator
- External temperature control up to 75°C with frost protection setting
- Glass lined steel tank
- Replaceable grey magnesium anode (inspect at least annually or more regularly in scale/ aggressive water conditions)
- Can be floor or wall mounted (bracket included)
- Supplied pressure relief valve must be fitted (set at 6 bar)
- Accessories may be required to comply with the Water Regulations – see AC69404 and AC69405
- Use a Thermostatic Mixing Valve to ensure water supply is maintained at a safe and constant temperature

6-AC69401-2022-V1

