

6 - Ventilation & Heating





AC6945

Instantaneous Inline Water Heater - 6 kW

For handwashing at a single basin
Heats water instantly as it flows through the unit
Energy efficient – no standing heat losses
Compact space saving design
Must be used with spray head taps with removable

Must be used with spray head taps with removable M22 / M24 nozzles

Simple to use and easy to install, cable pre-wired Non thermostatic

Not suitable for use with taps with thermostatic mixing valves

Bare wire heating system gives fast heat up time

Technical Specification	
Outer Casing	Easy clean, high impact ABS
Heating Element	Bare-wire heating (3 nickel chrome heating elements)
Taps & Spray Nozzles	Intended for use with spray head taps with removable M22/
	M24 nozzles. Supplied spray nozzle must be fitted.
Safety	Overheat temperature protection 80°C
IP Rating	IPX4
Installation	Must be installed in a frost free environment.
Plumbing	Min flow rate 2.0 l/m. Min water pressure 1 bar. Max rated
	pressure 7.5 bar. Water resistivity \geq 1300 $\Omega cm.$
Water Connection	Inlet/Outlet 2 x 1/2" BSP male. Fittings req (not supplied):
	2 x 15mm compression to 1/2" BSP female adapter.
Electrical Connection	Single phase. 27 amps. Cable pre-wired (0.7m).
Approvals	CE, WRAS
Standard Warranty	1 year parts or replacement warranty.

10-AC6945-2021-V1

