

9 - Renewables





AC92526

EV Basic Ped 7.4kW 2x Type 2 Skt

2x up to 7.4kW Type 2 Universal Socket - Black. Integrated (2x 2.3W) LED amenity lighting head. PME, AC overload & fault current and DC leakage protection.
Supports both DLB & SLM.
UK Smart Charge Point Regulations compliant.

| Technical Specification | |
|---------------------------------|---|
| Attribute | Value |
| Connection | 2x Type 2 Universal Socket |
| Output | Up to 7.4kW (32A) per socket |
| Input | 1-ph, 63A, 230V AC (+/- 10%) 50/60Hz |
| Standby Consumption | Up to 7.5W per soc (+ 4.6W LEDs if lit) |
| Communications | GSM, Wi-Fi, Ethernet, NFC, Bluetooth |
| Protection | Load Balancing, PME, DC Leak, |
| | Software and Physical Security |
| Environmental Protection | IP54, IK10 |
| Metering | MID |
| Dimensions | 205 x 205 x 1130 mm |
| Mass | < 15 kg |
| Enclosure Material | Aluminium/Polyethylene composite |
| Compliances | EN 61851, Smart Charge Points, |
| | OCPP 1.6J, UKCA and CE |

9-AC92526-2023-V1

